

Allgemeine Schmierempfehlungen

Kaliber	Hebelstein Sperrstift	Ankerrad	Unruhwelle	Groß- bodenrad	Räderwerk	Federhaus- welle	Feder und Schlepp- feder	Federhaus- wand	Automatik	Aufzug Kalender	Fraktion Zeiger- stellung	O-Ringe
5 - 8 3/4 ""	9415 941 8000	9010 8000	9010 8000	9020 8000	9010 8000	9020 SYNT-HP* 8000	8030	8213 Messing 8212 Alum. 8217	9010 9020 SYNT-HP*	8030 8200 8300	9501	8513
9 3/4 - 12 ""	9415 941 8000	9010 8000	9010 8000	SYNT-HP* D-5 8141	SYNT-HP* D-5 8141	SYNT-HP* D-5 8141	8200	8213 Messing 8212 Alum. 8217		8300 SYNT-HP* D-5	9501	8513
13 - 18 ""	9415 941 8000	9010 8000	9010 8000	SYNT-HP* D-5 8141	SYNT-HP* D-5 8141	SYNT-HP* D-5 8141	8200	8213 Messing 8212 Alum. 8217		8300 SYNT-HP* D-5	9501	8513
Chronometer	9415 941 8000	9010 8000	9010 8000	SYNT-HP* D-5 8141	SYNT-HP* D-5 8141	SYNT-HP* D-5 8141	8200	---	---	8200 8300	9501	8513
Roskopf und Stiftankeruhren	9010 941 8000	9010 8000	9010 8000	SYNT-HP* D/3 - D/5 8141	SYNT-HP* D/3 - D/5 8141	SYNT-HP* D-5 8141	8200	8213 Messing 8212 Alum. 8217	---	8200 8300	---	---
Wecker	9020 8030	9020 8030	9020 8030	SYNT-HP* D-5 8141	SYNT-HP* D-5 8141	SYNT-HP* D-5 8141	8200	---	---	8200 8300	---	---
Pendulen, Regulatoren	9020 8030	9020 8030	9020 8030	SYNT-HP* D-5 8141	SYNT-HP* D-5 8141	SYNT-HP* D-5 8141	8200 8201	---	---	8200 8300	---	---
Turm- und große Wanduhren	9020 8030	9020 8030	9020 8030	SYNT-HP* D-5 8141	SYNT-HP* D-5 8141	SYNT-HP* D-5 8141	8200 8201	---	---	8200 8300	---	---
	Rotorlager	Fortschaltung	Räderwerk									
Quartz Uhren Quartz Großuhren	9000 9024	9000 9027	9000 9024	---	---	---	---	---	---	8200 8300	9501	---

schwarz = optimale Schmierempfehlung
* Viskosität in Abhängigkeit der Kraftreserven auswählen